

---

## CHAPTER 6

# Projectiles

This chapter is the first in a series of chapters that discuss specific real-world phenomena and systems, such as projectile motion and airplanes, with the idea of giving you a solid understanding of their real-life behavior. This understanding will help you to model these or similar systems accurately in your games. Instead of relying on purely idealized formulas, I'll present a wide variety of practical formulas and data that you can use. I've chosen the examples in this and the next several chapters to illustrate common forces and phenomena that exists in many systems, not just the ones I'll be discussing here. For example, while Chapter 8 on ships discusses buoyancy in detail, buoyancy is not limited to ships; any object immersed in a fluid experiences buoyant forces. The same applies for the topics discussed in this chapter and Chapters 7, 9, and 10.

Once you understand what's supposed to happen with these and similar systems, you'll be in a better position to interpret your simulation results to determine whether they make sense, that is, whether they are realistic enough. You'll also be better educated on what factors are most important for a given system such that you can make appropriate simplifying assumptions to help ease your effort. Basically, when designing and optimizing your code, you'll know where to cut things out without sacrificing realism. This gets into the subject of *parameter tuning*.

Over the next few chapters I want to give you enough of an understanding of certain physical phenomena that you can tune your models for the desired behavior. If you are modeling several similar objects in your simulation but want each one to behave slightly differently, then you have to tune the forces that get applied to each object to achieve the varying behavior. Since forces govern the behavior of objects in your simulations, I'll be focusing on force calculations with the intent of showing you how and why certain forces are what they are instead of simply using the idealized formulas that I showed you in Chapter 3. Parameter tuning isn't just limited to tuning your model's behavior; it also involves dealing with numerical issues, such as numerical stability in your integration algorithms. I'll discuss these issues more when I show you several simulation examples in Chapters 12 through 17.

I've devoted this entire chapter to projectile motion because so many physical problems that may find their way into your games fall into this category. Further, the forces governing projectile motion affect many other systems that aren't necessarily projectiles; for example, the drag force experienced by projectiles is similar to that experienced by airplanes, cars, or any other object moving through a fluid such as air or water.

A projectile is an object that is placed in motion by a force acting over a very short period of time, which you know from Chapter 5 is also called an impulse. After the projectile is set in motion by the initial impulse, during the launching phase, the projectile enters into the projectile motion phase, in which there is no longer a thrust or propulsive force acting on it. As you know already from the examples presented in Chapters 2 and 4, there are other forces that act on projectiles. (For the moment I'm not talking about self-propelled "projectiles" such as rockets, since, owing to their propulsive force, they don't follow what I'll refer to as classical projectile motion until after they've expended their fuel.)

In the simplest case, neglecting aerodynamic effects, the only force acting on a projectile other than the initial impulsive force is gravitation. For situations in which the projectile is near the earth's surface, the problem reduces to a constant acceleration problem. Assuming that the earth's surface is flat, that is, that its curvature is large in comparison to the range of the projectile, the following statements describe projectile motion:

- The trajectory is parabolic.
- The maximum range, for a given launch velocity, occurs when the launch angle is  $45^\circ$ .
- The velocity at impact is equal to the launch velocity when the launch point and impact point are at the same level.
- The vertical component of velocity is zero at the apex of the trajectory.
- The time required to reach the apex is equal to the time required to descend from the apex to the point of impact, assuming that the launch point and impact point are at the same level.
- The time required to descend from the apex to the point of impact equals the time required for an object to fall the same vertical distance when dropped straight down from a height equal to the height of the apex.

## Simple Trajectories

There are four simple classes of projectile motion problems that I'll summarize:

- When the target and launch point are at the same level
- When the target is at a level higher than the launch point

- When the target is at a level lower than the launch point
- When the projectile is dropped from a moving system (such as an airplane) above the target

In the first type of problem the launch point and the target point are located on the same horizontal plane. Referring to Figure 6-1,  $v_0$  is the initial velocity of the projectile at the time of launch,  $\varphi$  is the launch angle,  $R$  is the range of the projectile, and  $h$  is the height of the apex of the trajectory.




Figure 6-1. Target and Launch Point at the Same Level

To solve this type of problem, use the formulas shown in Table 6-1. Note that in these formulas,  $t$  represents any time instant after launch and  $T$  represents the total time from launch to impact.

Table 6-1. Formulas: Target and Launch Point at Same Level

To Calculate:	Use This Formula:
$x(t)$	$(v_0 \cos \varphi)t$
$y(t)$	$(v_0 \sin \varphi)t - (gt^2)/2$
$v_x(t)$	$v_0 \cos \varphi$
$v_y(t)$	$v_0 \sin \varphi - gt$
$v(t)$	$\sqrt{v_0^2 - 2gtv_0 \sin \varphi + g^2t^2}$
$h$	$(v_0^2 \sin^2 \varphi) / (2g)$
$R$	$v_0 T \cos \varphi$
$T$	$(2v_0 \sin \varphi) / g$

Remember to keep your units consistent when applying these formulas. If you are working in the English system, all your length and distance values should be in feet (ft), time should be in seconds (s), speed should be in feet per second (ft/s), and acceleration

should be in feet per second squared ( $\text{ft/s}^2$ ). If you are using the SI (metric) system, length and distance values should be in meters (m), time should be in seconds (s), speed should be in meters per second (m/s), and acceleration should be in meters per second squared ( $\text{m/s}^2$ ). In the English system,  $g$  is  $32.2 \text{ ft/s}^2$ ; in the SI system,  $g$  is  $9.8 \text{ m/s}^2$ .

In the second type of problem the launch point is located on a lower horizontal plane than the target. Referring to Figure 6-2, the launch point's  $y$ -coordinate is lower than the target's  $y$ -coordinate.




Figure 6-2. Target Higher than Launch Point

For this type of problem, use the formulas shown in Table 6-2. Notice that most of these formulas are the same as those shown in Table 6-1.

Table 6-2. Formulas Target Higher than Launch Point

To Calculate:	Use This Formula:
$x(t)$	$(v_0 \cos \varphi)t$
$y(t)$	$(v_0 \sin \varphi)t - (gt^2)/2$
$v_x(t)$	$v_0 \cos \varphi$
$v_y(t)$	$v_0 \sin \varphi - gt$
$v(t)$	$\sqrt{v_0^2 - 2gtv_0 \sin \varphi + g^2 t^2}$
$h$	$(v_0^2 \sin^2 \varphi)/(2g)$
$R$	$v_0 T \cos \varphi$
$T$	$(v_0 \sin \varphi)/g + \sqrt{[2(h - b)]/g}$

Actually, the only formula that has changed is that for  $T$ , which has been revised to account for the difference in elevation between the target and the launch point.

In the third type of problem the target is located on a plane lower than the launch point; the target's  $y$ -coordinate is lower than the launch point's  $y$ -coordinate (see Figure 6-3).




Figure 6-3. Target Lower than Launch Point

Table 6-3 shows the formulas to use for this type of problem. Here again, almost all of the formulas are the same as those shown in Table 6-1.

Table 6-3. Formulas: Target Lower than Launch Point

To Calculate:	Use This Formula:
$x(t)$	$(v_0 \cos \varphi) t$
$y(t)$	$(v_0 \sin \varphi) t - (gt^2)/2$
$v_x(t)$	$v_0 \cos \varphi$
$v_y(t)$	$v_0 \sin \varphi - gt$
$v(t)$	$\sqrt{v_0^2 - 2gtv_0 \sin \varphi + g^2 t^2}$
$h$	$b + (v_0^2 \sin^2 \varphi) / (2g)$
$R$	$v_0 T \cos \varphi$
$T$	$(v_0 \sin \varphi) / g + \sqrt{(2h)/g}$

As in the second type of problem, the only formula that has changed is the formula for  $T$ , which has been revised to account for the difference in elevation between the target and the launch point (except this time the target is lower than the launch point).

Finally, the fourth type of problem involves dropping the projectile from a moving system, such as an airplane. In this case the initial velocity of the projectile is horizontal and equal to the speed of the vehicle dropping it. Figure 6-4 illustrates this type of problem.

Table 6-4 shows the formulas to use to solve this type of problem. Note here that when  $v_0$  is zero, the problem reduces to a simple free-fall problem in which the projectile simply drops straight down.




Figure 6-4. Projectile Dropped from a Moving System

Table 6-4. Formulas: Projectile Dropped from a Moving System

To Calculate:	Use This Formula:
$x(t)$	$v_0 t$
$y(t)$	$h - (gt^2)/2$
$v_x(t)$	$v_0$
$v_y(t)$	$-gt$
$v(t)$	$\sqrt{v_0^2 + g^2 t^2}$
$h$	$(gt^2)/2$
$R$	$v_0 T$
$T$	$\sqrt{(2h)/g}$

These formulas are useful if you're writing a game that does not require a more accurate treatment of projectile motion, that is, if you don't need or want to consider the other forces that can act on a projectile when in motion. If you are going for more accuracy, then you'll have to consider these other forces and treat the problem as we did in Chapter 4's example.

## Drag

In Chapters 3 and 4 I showed you the idealized formulas for viscous fluid dynamic drag as well as how to implement drag in the equations of motion for a projectile. This was illustrated in the example program discussed in Chapter 4. Recall that the drag force is a vector just like any other force and that it acts on the line of action of the velocity vector but in a direction opposing velocity. While those formulas work in a game simulation, as I said before, they don't tell the whole story. Although we can't treat the subject of

fluid dynamics in its entirety in this book, I do want to give you a better understanding of drag than just the simple idealized equation presented earlier.

It can be shown by analytical methods that the drag on an object moving through a fluid is proportional to its speed, size, and shape and the density and viscosity of the fluid through which it is moving. You can also come to these conclusions by drawing on your own real-life experience. For example, when waving your hand through the air, you feel very little resistance; however, if you put your hand out of a car window traveling at 60 mph, then you feel much greater resistance (drag force) on your hand. This is because drag is speed dependent. When you wave your hand under water, say, in a swimming pool, you'll feel a greater drag force on your hand than you do when waving it in the air. This is because water is more dense and viscous than air. As you wave your hand under water, you'll notice a significant difference in drag depending on the orientation of your hand. If your hand is such that your palm is in line with the direction of motion, that is, you are leading with your palm, then you'll feel a greater drag force than you would if your hand were turned 90 degrees as though you were executing a knife hand karate chop through the water. This tells you that drag is a function of the shape of the object. You get the idea.

To facilitate our discussion of fluid dynamic drag, let's look at the flow around a sphere moving through a fluid such as air or water. If the sphere is moving slowly through the fluid, the flow pattern around the sphere would look something like that shown in Figure 6-5.




Figure 6-5. Flow Pattern Around a Slowly Moving Sphere

*Bernoulli's equation*, which relates pressure to velocity in fluid flow, says that as the fluid goes around the sphere and speeds up, the pressure in the fluid (locally) will go down. The equation, presented by Daniel Bernoulli in 1738, applies to frictionless incompressible fluid flow and looks like this\*:

$$P/\gamma + z + V^2/(2g) = \text{constant}$$

where  $P$  is the pressure at a point in the fluid volume under consideration,  $\gamma$  is the specific weight of the fluid,  $z$  is the elevation of the point under consideration,  $V$  is the fluid velocity at that point, and  $g$  is the acceleration due to gravity. As you can see, if

\* In a real fluid with friction, this equation will have extra terms that account for energy losses due to friction.

the expression on the left is to remain constant, and assuming that  $z$  is constant, then if velocity increases, pressure must decrease. Likewise, if pressure increases, then velocity must decrease.

Referring to Figure 6-5, the pressure will be greatest at the stagnation point,  $S_1$ , and will decrease around the leading side of the sphere and then start to increase again around the back of the sphere. In an ideal fluid with no friction, the pressure is fully recovered behind the sphere, and there is a trailing stagnation point,  $S_2$ , whose pressure is equal to the pressure at the leading stagnation point. Since the pressure fore and aft of the sphere is equal and opposite, there is no net drag force acting on the sphere.

The pressure on the top and bottom of the sphere will be lower than that at the stagnation points, since the fluid velocity is greater over the top and bottom. Since this is a case of symmetric flow around the sphere, there will be no net pressure difference between the top and bottom of the sphere.

In a real fluid there is friction, which affects the flow around the sphere such that the pressure is never fully recovered on the aft side of the sphere. As the fluid flows around the sphere, a thin layer sticks to the surface of the sphere due to friction. In this *boundary layer* the speed of the fluid varies from zero at the sphere surface to the ideal free stream velocity as illustrated in Figure 6-6.




Figure 6-6. Velocity Gradient within a Boundary Layer

This velocity gradient represents a momentum transfer from the sphere to the fluid and gives rise to the frictional component of drag. Since a certain amount of fluid is *sticking* to the sphere, you can think of this as the energy required to accelerate the fluid and move it along with the sphere. (If the flow within this boundary layer is laminar, then the viscous shear stress between fluid “layers” gives rise to friction drag. When the flow is turbulent, the velocity gradient, and thus the transfer of momentum gives rise to friction drag.)

Moving further aft along the sphere, the boundary layer grows in thickness and will not be able to maintain its adherence to the sphere surface, and it will separate at some point. Beyond this *separation point*, the flow will be turbulent, and this is called the turbulent wake. In this region the fluid pressure is lower than that at the front of the sphere. This



pressure differential gives rise to the pressure component of drag. Figure 6-7 shows how the flow might look.




Figure 6-7. Flow Pattern Around a Sphere Showing Separation

For a slowly moving sphere the separation point will be approximately  $80^\circ$  from the leading edge.

Now, if you roughen the surface of the sphere, you'll affect the flow around it. As you would expect, this roughened sphere will have a higher friction drag component. However, more important, the flow will adhere to the sphere longer, and the separation point will be pushed further back to approximately  $115^\circ$ , as shown in Figure 6-8.




Figure 6-8. Flow Around a Roughened Sphere

This will reduce the size of the turbulent wake and the pressure differential, thus decreasing the pressure drag. It's paradoxical but true that, all other things being equal, a slightly roughened sphere will have less *total* drag than a smooth one. Have you ever wondered why golf balls have dimples? If so, there's your answer.

The total drag on the sphere depends very much on the nature of the flow around the sphere, that is, whether the flow is laminar or turbulent. This is best illustrated by looking at some experimental data. Figure 6-9 shows a typical curve of the total drag coefficient for a sphere plotted as a function of *Reynold's number*.

Reynold's number (commonly denoted  $N_r$  or  $R_n$ ) is a dimensionless number that represents the speed of fluid flow around an object. It's a little more than just a speed measure, since Reynold's number includes a characteristic length for the object and the viscosity and density of the fluid. The formula for Reynold's number is

$$R_n = (vL)/\nu$$

or

$$R_n = (vL\rho)/\mu$$




Figure 6-9. Total Drag Coefficient for a Smooth Sphere Versus Reynold's Number\*

where  $v$  is speed,  $L$  is a characteristic length of the object (diameter for a sphere),  $\nu$  is the kinematic viscosity of the fluid,  $\rho$  is the fluid mass density, and  $\mu$  is the absolute viscosity of the fluid. For Reynold's number to work out as a dimensionless number, velocity, length, and kinematic viscosity must have units of ft/s, ft, and ft<sup>2</sup>/s, respectively when working in the English system. In the SI system their units must be m/s, m, and m<sup>2</sup>/s, respectively.

This number is useful for nondimensionalizing data measured from tests on an object of given size (such as a model) such that the data can be scaled to estimate the data for similar objects of different size. Here, "similar" means that the objects are geometrically similar, just different scales, and that the flow pattern around the objects is similar. For a sphere the characteristic length is diameter, so you can use drag data obtained from a small model sphere of a given diameter to estimate the drag for a larger sphere of a different diameter. A more useful application of this scaling technique is estimating the viscous drag on ship or airplane appendages on the basis of model test data obtained from wind tunnel or tow tank experiments.

Reynold's number is used as an indicator of the nature of fluid flow. A low Reynold's number generally indicates laminar flow, while a high Reynold's number generally indicates turbulent flow. Somewhere in between, there is a transition range where the flow makes the transition from laminar to turbulent flow. For carefully controlled experiments, this transition (*critical*) Reynold's number can consistently be determined. However, in general the ambient flow field around an object, that is, whether it has low or high turbulence, will affect when this transition occurs. Further, the transition Reynold's number is specific to the type of problem being investigated, for example,

\* The curve shown here is intended to show the trend of  $C_d$  versus  $R_n$  for a smooth sphere. For more accurate drag coefficient data for spheres and other shapes, refer to any college-level fluid mechanics text, such as *Fluid Mechanics with Engineering Applications* by Daugherty, Franzini, and Finemore.

whether you're looking at flow within pipes, the flow around a ship, or the flow around an airplane, and so on.

The total drag coefficient,  $C_d$ , is calculated by measuring the total resistance,  $R_t$ , from tests and using the following formula:

$$C_d = R_t / (0.5 \rho v^2 A)$$

where  $A$  is a characteristic area that depends on the object being studied. For a sphere,  $A$  is typically the projected frontal area of the sphere, which is equal to the area of a circle of diameter equal to that of the sphere. By comparison, for ship hulls,  $A$  is typically taken as the underwater surface area of the hull. If you work out the units on the righthand side of this equation, you'll see that the drag coefficient is nondimensional, that is, it has no units.

Given the total drag coefficient, you can estimate the total resistance (drag) using the following formula:

$$R_t = (0.5 \rho v^2 A) C_d$$

This is a better equation to use than the ones given in Chapter 3, assuming that you have sufficient information available, namely, the total drag coefficient, density, velocity, and area. Note the dependence of total resistance on velocity squared. To get  $R_t$  in units of pounds (lb), you must have velocity in ft/s, area in ft<sup>2</sup>, and density in slug/ft<sup>3</sup> (remember,  $C_d$  is dimensionless). In the SI system you'll get  $R_t$  in newtons (N) if you have velocity in m/s, area in m, and density in kg/m<sup>3</sup>.

Turning back now to Figure 6-9, you can make a couple of observations. First you can see that the total drag coefficient decreases as Reynold's number increases. This is due to the formation of the separation point and its subsequent move aft on the sphere as Reynold's number increases and the relative reduction in pressure drag as discussed previously. At a Reynold's number of approximately 250,000 there is a dramatic reduction in drag. This is a result of the flow becoming fully turbulent with a corresponding reduction in pressure drag.

In the Cannon2 example in Chapter 4, I implemented the ideal formula for air drag on the projectile. In that case I used a constant value of drag coefficient that was arbitrarily defined. As I said earlier, it would be better to use the formula presented in this chapter for total drag along with the total drag coefficient data shown in Figure 6-9 to estimate the drag on the projectile. While this is more "accurate," it does complicate matters for you. Specifically, the drag coefficient is now a function of Reynold's number, which is a function of velocity. You'll have to set up a table of drag coefficients versus Reynold's number and interpolate this table given Reynold's number calculated at each time step. As an alternative, you can fit the drag coefficient data to a curve to derive a formula that you can use instead; however, the drag coefficient data may be such that you'll have to use a piecewise approach and derive curve fits for each segment of the drag coefficient curve. The sphere data presented herein is one such case. The data do not lend themselves nicely to a single polynomial curve fit over

the full range of Reynold's number. In such cases you'll end up with a handful of formulas for drag coefficient with each formula valid over a limited range of Reynold's numbers.

While the `Cannon2` example does have its limitations, it is useful to see the effects of drag on the trajectory of the projectile. The obvious effect is that the trajectory is no longer parabolic. You can see that the trajectory appears to drop off much more sharply when the projectile is making its descent after reaching its apex height.




Figure 6-10. *Cannon2 Example, Trajectories*

Another important effect of drag on trajectory (this applies to objects in free fall as well) is the fact that drag will limit the maximum vertical velocity attainable. This limit is the so-called *terminal velocity*. Take an object in free fall for a moment. As the object accelerates toward the earth at the gravitation acceleration, its velocity increases. As velocity increases, so does drag, since drag is a function of velocity. At some speed the drag force retarding the object's motion will increase to a point at which it is equal to the gravitational force that's pulling the object toward the earth. In the absence of any other forces that may affect motion, the net acceleration on the object is zero, and it continues its descent at the constant terminal velocity.

Let me illustrate this further. Go back to the formula I derived for the  $y$ -component (vertical component) of velocity for the projectile modeled in the `Cannon2` example. Here it is again so that you don't have to flip back to Chapter 4:

$$v_{y2} = (1/C_d)e^{(-C_d/m)t}(C_d v_{y1} + mg) - (mg)/C_d$$

It isn't obvious from looking at this equation, but the velocity component,  $v_{y2}$ , asymptotes to some constant value as time increases. To help visualize this, I've plotted this equation as shown in Figure 6-11.

As you can see, over time the velocity reaches a maximum absolute value of about  $-107.25$  speed units. The negative velocities indicate that the velocity is in the negative




Figure 6-11. Terminal Velocity

y-direction, that is, the object is falling toward the earth in this case. (For this calculation I arbitrarily assumed a mass of 100, a drag coefficient of 30, and an initial velocity of zero.)

Assuming an initial velocity of zero and equating the formula for total resistance shown earlier to the weight of an object, you can derive the following formula for terminal velocity for an object in free fall:

$$v_t = \sqrt{(2mg)/(C_d \rho A)}$$

The trick in applying this formula is in determining the right value for the drag coefficient. Just for fun, let's assume a drag coefficient of 0.5 and calculate the terminal velocity for several different objects. This exercise will allow you to see the influence of the object's size on terminal velocity. Table 6-5 gives the terminal velocities for various objects in free fall using an air density of  $2.37 \times 10^{-3}$  slug/ft<sup>3</sup> (air at standard atmospheric pressure at 60°F). Using this equation with density in slug/ft<sup>3</sup> means that  $m$  must be in slugs,  $g$  in ft/s<sup>2</sup>, and  $A$  in ft<sup>2</sup> to get the terminal speed in ft/s. I went ahead and converted from ft/s to miles per hour (mph) to present the results in Table 6-5. The weight of each object shown in this table is simply its mass,  $m$ , times  $g$ .

Table 6-5. Terminal Velocities for Various Objects

Object	Weight (lb)	Area (ft <sup>2</sup> )	Terminal Velocity (mph)
Skydiver in free fall	180	9	125
Skydiver with open parachute	180	226	25
Baseball (2.88-in. diameter)	0.32	0.045	75
Golf ball (1.65-in. diameter)	0.10	0.015	72
Raindrop (0.16-in. diameter)	$7.5 \times 10^{-5}$	$1.39 \times 10^{-4}$	20

Although I've talked mostly about spheres in this section, the discussions on fluid flow generally apply to any object moving through a fluid. Of course, the more complex the object's geometry, the harder it is to analyze the drag forces on it. Other factors such as surface condition and whether or not the object is at the interface between two fluids (such a ship in the ocean) further complicate the analysis. In practice, scale model tests are particularly useful. In the bibliography I give several sources where you can find more practical drag data for objects other than spheres.

## Magnus Effect

The *Magnus effect* (also known as the *Robbins effect*) is quite an interesting phenomenon. You know from the previous section that an object moving through a fluid encounters drag. What would happen if that object were spinning as it moved through the fluid. For example, consider the sphere that I talked about earlier and assume that while moving through a fluid such as air or water, it spins about an axis passing through its center of mass. What happens when the sphere spins is the interesting part: it actually generates lift! That's right—*lift*. From everyday experience, most people usually associate lift with a winglike shape such as an airplane wing or a hydrofoil. It is far less well known that cylinders and spheres can produce lift as well—that is, as long as they are spinning. I'll use the moving sphere to explain what's happening here.

From the previous section on drag, you know that for a fast-moving sphere there will be some point on the sphere where the flow separates, creating a turbulent wake behind the sphere. Recall that the pressure acting on the sphere within this turbulent wake is lower than the pressure acting on the leading surface of the sphere, and this pressure differential gives rise to the pressure drag component. When the sphere is spinning, say, clockwise about a horizontal axis passing through its center as shown in Figure 6-12, the fluid passing over the top of the sphere will be sped up, while the fluid passing under the sphere will be retarded.




Figure 6-12. Spinning Sphere

Remember, because of friction, there is a thin boundary layer of fluid that attaches to the sphere's surface. At the sphere's surface the velocity of the fluid in the boundary layer is zero relative to the sphere. The velocity increases within the boundary layer as you move farther away from the sphere's surface. In the case of the spinning sphere there is now a difference in fluid pressure above and below the sphere due to the increase in velocity above the sphere and the decrease in velocity below the sphere. Further, the separation point on the top side of the sphere will be pushed farther back along the sphere. The result is an asymmetric flow pattern around the sphere with a net lift force (due to the pressure differential) perpendicular to the direction of flow. If the surface of the sphere is roughened a little, not only will frictional drag increase, but this lift effect will increase as well.

Don't let the term "lift" confuse you into thinking that this force always acts to lift, or elevate, the sphere. The effect of this lift force on the sphere's trajectory is very much tied to the axis of rotation about which the sphere is spinning as related to the direction in which the sphere is traveling, that is, its angular velocity.

The magnitude of the Magnus force is proportional to the speed of travel, the rate of spin, density of fluid, the size of the object, and the nature of the fluid flow. This force is not easy to calculate analytically, and as with many problems in fluid dynamics you must rely on experimental data to accurately estimate this force for a specific object under specific conditions. There are, however, some analytical techniques that will allow you approximate the Magnus force. Without going into the theoretical details, you can apply the *Kutta-Joukowski theorem* to estimate the lift force on rotating objects such as cylinders and spheres. The Kutta-Joukowski theorem is based on a frictionless idealization of fluid flow involving the concept of circulation around the object (such as a vortex around the object). You can find the details of this theory in any fluid dynamics text (I give some references in the bibliography), so I won't go into the details here. However, I will give you some results.

For a spinning circular cylinder moving through a fluid you can use this formula to estimate the Magnus lift force:

$$F_L = 2\pi\rho Lvr^2\omega$$

where  $v$  is speed of travel,  $L$  is the length of the cylinder,  $r$  is its radius, and  $\omega$  is its angular velocity in radians per second (rad/s). If you have spin,  $n$ , in revolutions per second (rps), then  $\omega = 2\pi n$ . If you have spin,  $n$ , in revolutions per minute (rpm), then  $\omega = (2\pi n)/60$ .

For a spinning sphere moving through a fluid you can use this formula:

$$F_L = (2\pi^2\rho vr^4\omega)/(2r)$$

where  $r$  is the radius of the sphere. Consistent units for these equations would yield lift force in pounds in the English system or newtons in the SI system. In the English system density, speed, length, and radius have units of slugs/ft<sup>3</sup>, ft/s, and ft, respectively. In the SI system the appropriate units are for these quantities are kg/m<sup>3</sup>, m/s, and m, respectively.

Keep in mind that these formulas only approximate the Magnus force; they'll get you in the ballpark, but they are not exact and could be off by up to 50% depending on the situation. These formulas assume that there is no slip between the fluid and the rotating surface of the object, there is no friction, surface roughness is not taken into account, and there is no boundary layer.

At any rate, these equations will allow you to approximate the Magnus effect for flying objects in your games, where you'll be able to model the relative differences between objects of different size that may be traveling at different speeds with different spin rates. You'll get the look right. If numerical accuracy is what you're looking for, then you'll have to turn to experimental data for your specific problem.

Similar to the drag data shown in the previous section, experimental lift data are generally presented in terms of lift coefficient. Using an equation similar to the drag equation, you can calculate the lift force with the following equation:

$$F_L = (0.5\rho v^2 A)C_L$$

As usual, it's not as simple as this equation makes it appear. The trick is in determining the lift coefficient,  $C_L$ , which is a function of surface conditions, Reynold's number, velocity, and spin rate. Further, experiments show that the drag coefficient is also affected by spin.

For example, consider a golf ball struck perfectly (I wish) such that the ball spins about a horizontal axis perpendicular to its direction of travel while in flight. In this case the Magnus force will tend to lift the ball higher in the air, increasing its flight time and range. For a golf ball struck such that its initial velocity is 190 ft/s with a takeoff angle of 10 degrees the increase in range due to Magnus lift is on the order of 65 yards; thus, it's clear that this effect is significant. In fact, over the long history of the game of golf there has been an attempt to maximize this effect. In the late 1800s, when golf balls were still made with smooth surfaces, people observed that used balls with roughened surfaces flew even better than smooth balls. This observation prompted people to start making balls with rough surfaces so as to maximize the Magnus lift effect. The dimples that you see on modern golf balls are the result of many decades of experience and research and are thought to be optimum.

Typically, a golf ball takes off from the club with an initial velocity on the order of 250 ft/s, with a backspin on the order of 60 revolutions per second (rps). For these initial conditions the corresponding Magnus lift coefficient is within the range from 0.1 to 0.35. Depending on the spin rate, this lift coefficient can be as high as 0.45, and the lift force acting on the ball can be as much as 50% of the ball's weight.

If the golf ball is struck with a less than perfect stroke, the Magnus lift force may work against you. For example, if your swing is such that the ball leaves the club head spinning about an axis that is not horizontal, then the ball's trajectory will curve, resulting in a slice or a draw. If you top the ball such that the upper surface of the ball is spinning away from you, then the ball will tend to curve downward much more rapidly, significantly reducing the range of your shot.



As another example, consider a baseball that is pitched such that it is spinning with topspin about a horizontal axis perpendicular to its direction of travel. Here, the Magnus force will tend to cause the ball to curve in a downward direction, making it drop more rapidly than it would without spin. If the pitcher spins the ball such that the axis of rotation is not horizontal, then the ball will curve out of the vertical plane. Another trick that pitchers use is to give the ball backspin, making it appear (to the batter) to actually rise. This rising fast ball does not actually rise, but because of the Magnus lift force, it falls much less rapidly than it would without spin.

For a typical pitched speed and spin rate of 148 ft/s and 30 rps, respectively, the lift force can be up to 33% of the ball's weight. For a typical curve ball the lift coefficient is within the range of 0.1 to 0.2, and for fly balls it can be up to 0.4.

These are only two examples, however; you need not look far to find other examples of the Magnus force in action. Think about the behavior of cricket balls, soccer balls, tennis balls, or Ping-Pong balls when they spin in flight. Bullets fired from a gun with a rifling barrel also spin and are affected by this Magnus force. There have even been sailboats built with tall vertical rotating cylindrical "sails" that use the Magnus force for propulsion. I've also seen technical articles describing a propeller with spinning cylindrical blades instead of airfoil-type blades.

To further illustrate the Magnus effect, I have prepared a simple program that simulates a ball being thrown with varying amounts of backspin (or topspin). This example is based on the cannon example, so here again, the code should look familiar to you. In this example I've neglected drag, so the only forces that the ball will see are due to gravity and the Magnus effect. I did this to isolate the lift-generating effect of spin and to keep the equations of motion clearer.

Since most of the code for this example is identical, or very similar, to that in the previous cannon examples, I won't repeat it here. I will, however, show you the global variables used in this simulation along with a revised `DoSimulation` function that takes care of the equations of motion:

```
//-----//
// Global variables required for this simulation
//-----//
TVector      V1;      // Initial Velocity (given), m/s
TVector      V2;      // Velocity vector at time t, m/s
double       m;       // Projectile mass (given), kg
TVector      s1;      // Initial position (given), m
TVector      s2;      // The projectile's position (displacement) vector, m
double       time;    // The time from the instant the projectile
                        // is launched, s
double       tInc;    // The time increment to use when stepping
                        // through the simulation, s
double       g;       // acceleration due to gravity (given), m/s^2
double       spin;    // spin in rpm (given)
double       omega;   // spin in radians per second
double       radius;  // radius of projectile (given), m

#define      PI      3.14159f
#define      RHO     1.225f      // kg/m^3
```

```
//-----//
int DoSimulation(void)
//-----//
{
    double C = PI * RHO * RHO * radius * radius * radius * omega;
    double t;

    // step to the next time in the simulation
    time+=tInc;
    t = time;

    // Calc. V2:
    V2.i = 1.0f/(1.0f-(t/m)*(t/m)*C*C) * (V1.i + C * V1.j * (t/m) -
        C * g * (t*t)/m);
    V2.j = V1.j + (t/m)*C*V2.i - g*t;

    // Calc. S2:
    s2.i = s1.i + V1.i * t + (1.0f/2.0f) * (C/m * V2.j) * (t*t);
    s2.j = s1.j + V1.j * t + (1.0f/2.0f) * ( ((C*V2.i) - m*g)/m ) * (t*t);

    // Check for collision with ground (xz-plane)
    if(s2.j <= 0)
        return 2;

    // Cut off the simulation if it's taking too long
    // This is so the program does not get stuck in the while loop
    if(time>60)
        return 3;

    return 0;
}
```

The heart of this simulation are lines that calculate  $v_2$  and  $s_2$ , the instantaneous velocity and position of the projectile, respectively. The equations of motion here come from the 2D kinetic equations of motion including gravity, as discussed in Chapter 4, combined with the following formula (shown earlier) for estimating the Magnus lift on a spinning sphere:

$$F_L = (2\pi^2 \rho v r^4 \omega) / (2r)$$

You can see the effect of spin on the projectile's trajectory by providing the sample program with different values for spin in revolutions per minute. The program converts this to radians per second and stores this value in the variable `omega`. A positive spin value indicates bottom spin such that the bottom of the sphere is spinning away from you; a negative spin indicates topspin, in which the top of the ball spins away from you. Bottom spin generates a positive lift force that will tend to extend the range of the projectile; topspin generates negative lift that will force the projectile toward the ground, shortening its range. (Note that this example assumes that the spin axis is horizontal and perpendicular to the plane of the screen.) Figure 6-13 illustrates this behavior.

## Variable Mass

Earlier in this book I mentioned that some problems in dynamics involve variable mass. We'll look at variable mass here, since it applies to self-propelled projectiles such




Figure 6-13. Magnus Effect Sample Program

as rockets. When a rocket is producing thrust to accelerate itself, it loses mass (fuel) at some rate. When all of the fuel is consumed (burnout), the rocket no longer produces thrust and has reached its maximum speed. After burnout you can treat the trajectory of the rocket just as you would a non-self-propelled projectile, as discussed earlier. However, while the rocket is producing thrust, you need to consider its mass change, since this will affect its motion.

In cases in which the mass change of the object under consideration is such that the mass being expelled or taken in has zero absolute velocity, like a ship consuming fuel, for example, you can set up the equations of motion as you normally would, where the sum of the forces equals the rate of change in momentum. However, in this case mass will be a function of time, and your equations of motion will look like this:

$$\sum F = ma = d/dt(mv) = m(dv/dt) + (dm/dt)v$$

You can proceed to solve them just as you would normally but keeping in mind the time dependence of mass.

A rocket, on the other hand, expels mass at some nonzero velocity, and you can't use the above approach to properly account for its mass change. In this case you need to consider the relative velocity between the expelled mass and the rocket itself. The linear equation of motion now looks like this:

$$\sum F = m dv/dt + dm/dt u$$

where  $u$  is the relative velocity between the expelled mass and the object (the rocket, in this case).

For a rocket traveling straight up, neglecting air resistance and the pressure at the exhaust nozzle, the only force acting on the rocket is due to gravity. But the rocket is expelling mass (burning fuel). How it expels this mass is not important here, since the forces involved there are internal to the rocket; we need only consider the external forces. Let

the fuel burn rate be  $-m'$ . The equation of motion (in the vertical direction) for the rocket is as follows:

$$\begin{aligned}\sum F &= m \, dv/dt + dm/dt \, u \\ -mg &= m \, dv/dt - m' u\end{aligned}$$

If you rearrange this so that it looks as though there's only an  $ma$  term on the right of the equation, you get

$$m' u - mg = m \, dv/dt = ma$$

Here you can see that the thrust that propels the rocket into the air is equal to  $m' u$ . Since the fuel burn rate is constant, the mass of the rocket at any instant in time is equal to

$$m = m_0 - m' t$$

where  $m_0$  is the initial mass and the burn rate,  $m'$ , is in the form mass per unit time.